

NOTES

- TI. THE BASE SLAB SHALL BE POURED MONOLITHICALLY WITH BOTTOM RISER SECTION. PRECAST MANHOLE BASES SHALL FIT THE CONDITIONS AND LOCATIONS FOR WHICH THEY ARE INTENDED WITHOUT ANY FIELD MODIFICATIONS.
- 2. PRECAST MANHOLE BASES SHALL BE BEDDED ON AN APPROVED GRANULAR BEDDING MATERIAL, PER SPECIFICATIONS.
- WHEN TYING INTO EXISTING MANHOLE PENETRATION MUST BE CORE-DRILLED AND CONNECTION MUST BE MADE USING LINK SEAL OR APPROVED EQUAL AND WATER TIGHT.
- 3.1. NEW FLOW-LINE MUST BE AT OR SLIGHTLY ABOVE EXISTING AND MUST SWEEP TO ALLOW SMOOTH TRANSITION TO DOWNSTREAM FLOW
- SET EACH MANHOLE RING (OUTER AND INNER JOINT) IN TWO (2)
 FULL BEDS OF BITUMINOUS MASTIC (RAMNECK) OR PLASTIC
 SEALING COMPOUND.
- 5. DESIGN PLANS SHALL INDICATE INVERT (INLET AND OUTLET) ELEVATIONS.
- MANHOLE TO PIPE CONNECTIONS SHALL BE CONSTRUCTED WITH A COMPRESSION-TYPE FLEXIBLE CONNECTOR, CAST INTO THE MANHOLE WALL PER SPECIFICATIONS.
- 7. MANHOLE SHALL BE WATER TIGHT.
- VERTICAL ADJUSTMENT RINGS SHALL BE SEALED WITH AN EXTRUDED BUTYL ADHESIVE TAPE (EZ-WRAP BY PRESS-SEAL GASKET CORP. OR EQUAL).
- 9. STUB OUT ONE STICK PAST MANHOLE AT DEAD-END MANHOLES.
- 10. SEWER TAPS LARGER THAN 4" REQUIRE A MANHOLE.
- 11. MANHOLES DEEPER THAN 15 FEET SHALL BE 60" IN DIAMETER.
- 12. FORMED FLOW CHANNEL IN BENCH SHALL MATCH O.D. OF PIPE.

- 13. IF MANHOLE LID IS IN PAVEMENT RECESS IT 0.5".
- 14. WHEN TIEING INTO A HIGH FLOW SEWER INVERT OF CONNECTING SEWER SHALL MATCH CROWN OF EXISTING SEWER
- 15. MANHOLE INTERIOR COATING SHALL BE REQUIRED IN ANTICIPATED HIGH H₂S AREAS, AS DETERMINED BY DISTRICT FINGINFER
- 16. ALL MANHOLES WITH ECCENTRIC CONES SHALL BE ALIGNED WITH THE MANHOLE LIDS TOWARD THE ROAD CENTERLINE.
- 17. ALL OUTSIDE JOINTS OF RISER RINGS SHALL BE GROUTED, USING MORTAR MIXED WITH TYPE-V CEMENT.
- ALL MANHOLES MUST PASS A VACUUM PRESSURE TEST, AS OUTLINED IN SEWER NOTES.
- CONCRETE IN POURED BASES MUST BE VIBRATED TO ENSURE THERE ARE NO AIR POCKETS.

