

## NOTES:

- $\overline{\rm 1.~SAM}$  PLING STATIONS SHALL BE 4.5' BURY WITH A % " FIP INLET AND AN UNTHREADED NOZZLE.
- 2. ALL STATIONS SHALL BE ENCLOSED IN A LOCKABLE, NON-REMOVEABLE ALUMINUM-CAST HOUSING.
- 3. WHEN OPENED, THE STATION SHALL REQUIRE NO KEY FOR OPERATION AND THE WATER WILL FLOW IN AN ALL BRASS WATERWAY.
- ALL WORKING PARTS SHALL ALSO BE OF BRASS AND REMOVEABLE FROM ABOVE GROUND WITHOUT DIGGING. EXTERIOR PIPE SHALL BE BRASS OR GALVANIZED.
- A COPPER VENT TUBE WILL ENABLE EACH STATION TO BE PUMPED FREE OF STANDING WATER TO PREVENT FREEZING AND TO MINIMIZE BACTERIA GROWTH.
- 6. ECLIPSE NO. 88-SS SAMPLING STATION SHALL BE MANUFACTURED BY KUPFERLE FOUNDRY, ST. LOUIS, MO.

CONTRACTOR SUPPLIED MATERIALS:				
ITEM	MATERIALS			
CURB STOP	MUELLER (B25209), FORD BALL (TYPE B44-333-Q) OR EQUAL			
SERVICE LINE	TYPE "K" COPPER (CONTINUOUS, NO FITTINGS)			
CURB BOX	TYLER SERIES 6500 W/ ADJUSTABLE SERVICE BOX (#94E)			
BEDDING MATERIAL	WASHED SAND OR SQUEEGEE MATERIAL			

DISTRICT SUPPLIED MATERIALS:		
3/4" AND 1" TAPS		
CORPORATION STOP		
INSULATOR		
SADDLE ON PVC MAINS		

14806 WEST 52ND AVENUE GOLDEN, COLORADO 80403-1228				
	DWG. NO			
SCALE:	NTS	SAMPLING STATION		
REV DATE:	06/2015			